

BI120S Universal 120 Watt Series

- 100-240 Vac Universal Input
- Meets "ENERGY STAR" Program Requirements
- Single Output to 120W
- Regulated Output with Low Ripple
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Modified and Custom Designs Also Available
- Desktop Style


RoHS


Model	Output Voltage DC (V)	Maximum Current (A)	Maximum Watts (W)	Ripple & Noise Vp-p max. (mV)
BI120-S-12-X-XX	12	10.00	120.0	120
BI120-S-15-X-XX	15	8.00	120.0	150
BI120-S-18-X-XX	18	6.67	120.1	180
BI120-S-24-X-XX	24	5.00	120.0	240
BI120-S-48-X-XX	48	2.50	120.0	480

Input Specification

Input Voltage Range	100 to 240VAC -10%, +10%
Line Frequency	47 to 63 Hz
Input Current	2.0A max. at 90VAC Input
Protection	Internal Primary Current Fuse, Inrush Limiting

Output Specification

Line & Load Regulation (at End of Cable)	Line Regulation	+/- 1%
	Load Regulation	+/- 5%
Ripple & Noise	1% Vp-p max.	
Transient Response	0.5ms for 50% Load change Typ.	
Protection	Over-current Protection (Hiccup)	
	Over-voltage Protection (OVP)	
	Short Circuit Protection	

Environmental Specification

Operating Temperature	0°C to 40°C with no derating
Relative Humidity	5% to 95% non-condensing
Altitude	0 - 16,000 feet
Cooling	Convictional - Non vented case

Input Configuration



IEC320

C14 (F)



IEC320

C18 (Q)



IEC320

C8 (N)

Specify the input configuration Code in your Order.

General Specification

Topology	Switching - Fixed Frequency Flyback
Leakage Current	Less than 250uA
Dielectric Withstand	3,000VAC Primary - Secondary 1800AC Primary - F.G 500VDC Secondary - F.G
Storage Temperature	-30 °C to 85 °C
Efficiency	Minimum Average Efficiency in Active Mode ≥ 88%
Hold-up Time	20ms min. @115VAC
EMI	Complies with EMC Directives
Max. Power in No-Load	≤ 0.21W @115VAC & 230VAC
MTBF	250,000 Calculated Hours Minimum.
Approvals and Safety Standards	UL60950-1, IEC/EN60950-1, K60950-1 EMC : EN55022 / 55024 / 61000
Case and Dimension	8.2(L) x 2.5(W) x 1.6(H) [in] 209.4(L) x 64.4(W) x 41.5(H) [mm]
Case Material	Black 94V0 Polycarbonate
Cord and Connectors	16 AWG or 18 AWG 1,200mm 4 Conductor. Other cable and connectors are available.

Part Number Key

BI120	S	12	X
Product Family Name	Single Output	Volt (DC)	Input Configuration

