

BPM150S Universal 150 Watt Series

- 100-240 Vac Universal Input
- Meets "ENERGY STAR" Program Requirements
- Single Output to 150W
- Regulated Output with Low Ripple
- Meets Medical Safety Agency Requirements
- CE Compliant
- Impact Resistant Polycarbonate Enclosure
- Modified and Custom Designs Also Available
- Desktop Style



Model	Output Voltage DC (V)	Maximum Current (A)	Maximum Watts (W)	Ripple & Noise Vp-p max. (mV)
BPM-150-S-12-X-XX	12	12.50	150.0	120
BPM-150-S-15-X-XX	15	10.00	150.0	150
BPM-150-S-18-X-XX	18	8.30	149.4	180
BPM-150-S-24-X-XX	24	6.25	150.0	240

Input Specification

Input Voltage Range	100 to 240VAC -10%, +10%
Line Frequency	47 to 63 Hz
Input Current	3.0A max. at 90VAC Input
Protection	Internal Primary Current Fuse, Inrush Limiting

Output Specification

Line & Load Regulation	Line Regulation	+/- 1%
(at End of Cable)	Load Regulation	+/- 5%
Ripple & Noise	1% Vp-p max.	
Transient Response	0.5ms for 50% Load change Typ.	
Protection	Over-current Protection (Hiccup)	
	Short Circuit Protection	

Environmental Specification

Operating Temperature	0°C to 40°C with no derating
Relative Humidity	5% to 95% non-condensing
Altitude	0 - 10,000 feet
Cooling	Convectional - Non vented case

Input Configuration



IEC320
C14 (F)

Specify the input configuration Code in your Order.

General Specification

Topology	Switching - Half bridge
Leakage Current	Less than 100uA
Dielectric Withstand	5,656VDC Primary - Secondary 2,150VDC Primary - F.G 500VDC Secondary - F.G
Storage Temperature	-30 °C to 85 °C
Efficiency	87% min
Hold-up Time	18ms min. @ 120VAC
EMI	Complies with EMC Directives
MTBF	100,000 Calculated Hours Minimum.
Approvals and Safety Standards	UL60601-1, IEC/EN60601-1, K60950-1 EMC : EN60601-1-1-2 / EN55011
Case and Dimension	8.2(L) x 2.5(W) x 1.6(H) [in] 209.4(L) x 64.4(W) x 41.5(H) [mm]
Case Material	Black 94V0 Polycarbonate
Cord and Connectors	T.B.D Other cable and connectors are available.

Part Number Key

<u>BPM150</u>	<u>S</u>	<u>12</u>	<u>X</u>	<u>XX</u>
Product Family Name	Single Output	Volt (DC)	Input Configuration	Customer Number