

# JPW190KB Universal 85-90 Watt Series

- 100-240 Vac Universal Input
- Meets "ENERGY STAR" Program Requirements
- Single Output to 85-90W
- Regulated Output with Low Ripple
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Modified and Custom Designs Also Available
- Desktop Style



Model	Output Voltage DC (V)	Maximum Current (A)	Maximum Watts (W)	Ripple & Noise Vp-p max. (mV)
JPW190-KB-12-XX-X-XX	12	7.00	84.0	120
JPW190-KB-13-XX-X-XX	13.5	6.00	81.0	135
JPW190-KB-15-XX-X-XX	15	6.00	90.0	150
JPW190-KB-18-XX-X-XX	18	5.00	90.0	180
JPW190-KB-24-XX-X-XX	24	3.75	90.0	240
JPW190-KB-48-XX-X-XX	48	1.87	89.8	480

## Input Specification

Input Voltage Range	100 to 240VAC -10%, +10%
Line Frequency	47 to 63 Hz
Input Current	2.0A max. at 90VAC Input
Protection	Internal Primary Current Fuse, Inrush Limiting


## Output Specification

Line & Load Regulation (at End of Cable)	Line Regulation	+/- 1%
	Load Regulation	+/- 5%
Ripple & Noise	1% Vp-p max.	
Transient Response	0.5ms for 50% Load change Typ.	
Protection	Over-current Protection (Hiccup)	
	Short Circuit Protection	

## Environmental Specification

Operating Temperature	0°C to 40°C with no derating
Relative Humidity	5% to 95% non-condensing
Altitude	0 - 10,000 feet
Cooling	Convictional - Non vented case

## Input Configuration



Specify the input configuration Code in your Order.

## General Specification

Topology	Switching - Fixed Frequency Flyback
Leakage Current	Less than 250uA
Dielectric Withstand	4,242VDC Primary - Secondary
	2,150VDC Primary - F.G
	500VDC Secondary - F.G
Storage Temperature	-30 °C to 85 °C
Efficiency	Minimum Average Efficiency in Active Mode ≥ 87%
Hold-up Time	18ms min. @115VAC
EMI	Complies with EMC Directives
Max. Power in No-Load	≤ 0.5W
MTBF	100,000 Calculated Hours Minimum.
Approvals and	UL60950-1, IEC/EN60950-1, K60950-1
Safety Standards	EMC : EN55022 / 55024 / 61000
Case and Dimension	5.08(L) x 3.05(W) x 1.59(H) [in]
	129(L) x 77(W) x 40(H) [mm]
Case Material	Black 94V0 Polycarbonate
Cord and Connectors	18 AWG 1,500mm 4 Conductor.
	Other cable and connectors are available.

## Part Number Key

<u>JPW190</u>	<u>KB</u>	<u>12</u>	<u>XX</u>	<u>X</u>	<u>XX</u>
Product Family Name	Design Revision Change	Volt (DC)	Connector Number	Input Configuration	Customer Number